

Declaration of Performance

DOP Number 1340 -2021

- 1, Unique identification code of the product-type: Cementitious Flooring Screed
- 2, Type, batch or serial number or any other element allowing identification of the construction product: **CT-C30-F3**
- 3, Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious Levelling Screed, for the use internally in buildings – Non wearing surface

- 4, Name, registered trade name or registered trade mark and contact address of the manufacturer:
 - S. Morris Ltd, Tout Quarry, Charlton Adam, Somerton, Somerset, TA11 7AN
- 5, In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 13813:2002 Screed material and floor screeds - Screed material - Properties and Requirements

6, Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire (for exposed situations)	A1	BS EN 13813:2002
Release of Corrosive substances	СТ	
Compressive Strength	30 N/mm ²	
Flexural Strength	3 N/mm²	

<u>Note:</u> Information on dangerous substances will only be given when and where required in the appropriate form.

7, The performance of the product identified in points 1 and 2, are in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Certificate Number: 753486

Certification body detail: BSI, Kitemark Court, Davy Ave, Knowlhill, Milton Keynes, MK5 8PP

The cementitious flooring screed products detailed above are compliant in accordance with the assignation of evaluation of conformity under section 9, table 12, EN 13813:2002.

Darren Radford - Technical Manager, S. Morris Ltd



S. Morris Ltd Tout Quarry, Charlton Adam, Somerton, Somerset, TA11 7AN

CT-C30-F3

BS EN 13813

Cementitious screed material for use internally in buildings

Reaction to fire A1

Release of Corrosive substances CT

Compressive Strength 30 N/mm²

Flexural Strength 2 N/mm²

Note: Information on Dangerous Substances will only be given out when and where required in

the appropriate form. Refer to BS EN 13813:2002, Annex ZA.3

Certificate number: **753486**

Certification Body details: BSI, Kitemark Court, Davy Ave, Knowlhill, Milton Keynes, MK5 8PP