

S Morris Ltd Tout Quarry Charlton Adam Somerset, TA11 7AN

Declaration of Performance Certificate Number: **0201**

1. Product-type: 100mm Dense 7.3N

2. Identification of the construction product: Category I – Aggregate Concrete Masonry Unit

3. Intended use or uses of the construction product: Annex ZA - Masonry used in walls, columns and partitions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

S Morris Ltd, Tout Quarry, Charlton Adam, Somerton, Somerset, TA11 7AN

5. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 771-3:2011+A1:2015 - Specification for masonry units. Aggregate concrete masonry units

6. Declared performance

Essential Characteristics		Performance	Harmonised
			Technical
			Specification
Dimensions	Length (mm)	440	EN 771-3:2011
	Width (mm)	100	+A1:2015
	Height (mm)	215	
Dimensional Tolerance		D1, Flatness NPD, Parallelism NPD	
Dimensional Stability	Moisture movement, N/mm ²	0.30mm/m	
Configuration	Shape & features	NPD	
	Group according to EN 1996-1	Group 1	
Compressive Strength	Mean compressive Strength	7.3 N/mm ²	
	Direction of Load	Perpendicular to bed face	
	Unit category	Category II	
Bond Strength	Shear bond strength	0.15 N/mm ²	
	Flexural bond strength	NPD	
Reaction to fire		Euro Class A1 (Commission	
		decision 2000/605/EC)	
Water Absorption		20 g/m ² s	
Water Vapour Diffusion		30/100μ	
Direct Airborne Sound	Gross density	1850 kg/m³	
insulation	Configuration, dimensions &	Configuration as above	
	Tolerance		
Thermal Conductivity,		1.11 W/m.K [$\lambda_{10,dry}$] p = 50%	
Durability against freeze thaw		For use below and above ground	
Dangerous Substances		See Note	

Note: Information on dangerous substances will only be given when and where required in the appropriate form.

The performance of the product identified in points 1 and 2, are in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Certificate number: 0086-CPD-597868

Certification Body details: BSI, Kitemark Court, Davy Ave, Knowlhill, Milton Keynes, MK5 8PP

The Aggregate Concrete Masonry products detailed above are compliant in accordance with the Assignation of Evaluation of Conformity under System 2+, Table ZA.2, EN 771-3:2011+A1:2015.

Darren Radford - Technical Manager, S. Morris Ltd 16th September 2022

CONFORMITY CERTIFICATE/ DECLARATION OF PERFORMANCE - ISSUE 2 – 16/09/2022



S Morris Ltd Tout Quarry Charlton Adam Somerset, TA11 7AN



S Morris Ltd

Tout Quarry, Charlton Adam, Somerton, Somerset, TA11 7AN

EN 771-3:2011+A1:2015 100mm Dense 7.3N

Category I – 440mm x 100mm x 215mm Aggregate Concrete Masonry Unit Annex ZA - Masonry used in walls, columns and partitions

Dimensions: Length; 440mm

Width; 100mm

Height; 215mm

Dimensional Tolerance: Category; D1 (Flatness NPD, Plane Parallelism NPD)

Configuration; Group 1

Dimensional Stability: Moisture movement; 0.30mm/m

Mean Compressive Strength: Characteristic; 7.3 N/mm² [L bed face]

Shear Bond: Fixed Value; 0.15 N/mm²

Flexural Bond: NPD

Reaction to Fire Euro class A1 (Commission decision 2000/605/EC)

Water Absorption:Mean20 g/m²sWater Vapour Diffusion:30/100μ

Direct Airborne Sound Insulation: Typical Gross Dry 1850 kg/m³

(Configuration as above)

Thermal Conductivity: P=50% 1.11 W/ (m.k) [λ 10, dry]

Durability against freeze/ thaw:For use below and above ground

Dangerous substances: See Note

Note: Information on Dangerous Substances will only be given out when and where required in the

appropriate form. Refer to BS EN 771-3:2011, Annex ZA3.

Certificate number: **0086-CPD-597868**

Certification Body details: BSI, Kitemark Court, Davy Ave, Knowlhill, Milton Keynes, MK5 8PP